

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: MK-6HY EXP0.25, MK-6HY EXP0.50
MSDS ID Number: Z-01787

MSDS Date: 06/17/2010

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: MK-6HY EXP0.25, MK-6HY EXP0.50
MSDS Number: Z-01787
Cancelled MSDS Number: Z-01776
MSDS Date: 06/17/2010
Chemical Family Name: Lightweight Gypsum Aggregate Plaster
Product Use: Fireproofing Product.
Chemical Formula: Mixture-NA
CAS # (Chemical Abstracts Service Number): Mixture-NA

Manufactured by:

W.R.Grace & Co.-Conn.
62 Whittemore Avenue
Cambridge, MA 02140

Grace Canada, Inc.
294 Clements Road West
Ajax, Ontario L1S 3C6

In Case of Emergency Call:

In USA: (617) 876-1400 In Canada: (905) 683-8561

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS#	Percent (max)
Calcium Carbonate.	1317-65-3	1-10
Calcium sulfate	007778-18-9	50-100
Cellulose.	65996-61-4	1-10
Polystyrene	009003-53-6	1-10
Quartz	014808-60-7	1-10

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview:

Caution!

Irritating to eyes, skin and respiratory system.
Prolonged exposure may cause risk of lung disease (i.e. silicosis and/or lung cancer).

HMIS Rating:

Health: 1*
Flammability: 0
Reactivity: 0
Personal Protective Equipment: B (See Section 8)

Potential Health Effects:

Inhalation: Irritating if inhaled resulting in coughing and sneezing.
May aggravate chronic respiratory conditions such as asthma or bronchitis.
Long term inhalation of dust may increase risk of contracting pneumoconiosis ("dusty lungs") and decrease lung function.
Prolonged inhalation of respirable crystalline silica dust can result in lung disease (i.e. silicosis and/or lung cancer). Symptoms include coughing, shortness of breath, wheezing and reduced pulmonary function.
Eye Contact: Eye contact causes irritation.
Skin Contact: Skin contact causes irritation.
May dry skin.
During hardening (rehydration) this product may slowly develop sufficient heat to cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or while in continuous, prolonged contact with the skin.
Skin Absorption: Not expected to be harmful if absorbed through the skin.
Ingestion: Ingestion not expected to be harmful.

W. R. GRACE

MATERIAL SAFETY DATA SHEET

Product Name: MK-6HY EXP0.25, MK-6HY EXP0.50

MSDS ID Number: Z-01787

MSDS Date: 06/17/2010

SECTION 4 - FIRST AID MEASURES:

Skin Contact: Wash with soap and water.

If discomfort or irritation persists, consult a physician.

Remove contaminated clothing and wash before reuse.

Eye Contact: Flush eyes with water for at least 15 minutes while holding eyelids open.

If discomfort or irritation persists, consult a physician.

Ingestion: Do not induce vomiting.

Never give anything by mouth to an unconscious person.

If discomfort or irritation persists, consult a physician.

Inhalation: If symptoms develop, get fresh air. If symptoms persist, consult a physician.

If breathing has stopped, give artificial respiration then oxygen if needed.

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

Flash Point: Not Applicable

Flash Point Method: Not Applicable

Lower Explosion Limit: Not Available

Upper Explosion Limit: Not Available

Auto-Ignition Temperature: Not Available

NFPA Rating:

Health: 1

Flammability: 0

Reactivity: 0

Extinguishing Media: Not Applicable. Product will not burn.

Special Fire Fighting Procedures: None

No special procedures specific to this product.

Unusual Fire and Explosion Hazards: None unless noted below.

SECTION 6 - ACCIDENTAL RELEASE MEASURES:

Spills/Leaks: Use proper personal protective equipment. Do not flush to sewer or allow to enter waterways. Keep unnecessary people away.

If spilled, prevent material from entering water systems. Observing the listed Precautionary Measures found in Section 7 of this document. Dry spills should be immediately swept up and placed in a suitable container to prevent further release of material. Slurry spills should be immediately contained (to minimize the extent of the spill) and absorbed with an inert, non-combustible material. Place material in a suitable container to prevent further release.

SECTION 7 - HANDLING AND STORAGE

Precautionary Measures: Avoid contact with eyes, skin and clothing.

Avoid creating and inhaling airborne dust or particulates.

Practice good personal hygiene to avoid ingestion.

Use only with adequate ventilation.

Wash clothing before reuse.

Equip mixers with dust covers.

Provide respiratory protection if needed.

Wear skin and eye protection to avoid contact with dust or spray.

Post "Slippery When Wet" signs where appropriate.

Use anti-slip surfaces on working platforms.

FOR PROFESSIONAL USE ONLY. KEEP OUT OF CHILDREN'S REACH.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT

EXPOSURE GUIDELINES (US)

Ingredient	ACGIH TLV			OSHA PEL			Other
	TWA	STEL	Ceiling	TWA	STEL	Ceiling	
Calcium Carbonate.	10 mg/m3 TWA (particulate matter containing no asbestos)	-	-	-	-	-	-

W. R. GRACE**MATERIAL SAFETY DATA SHEET**

Product Name: MK-6HY EXP0.25, MK-6HY EXP0.50

MSDS ID Number: Z-01787

MSDS Date: 06/17/2010

	and <1% crystalline silica)						
Calcium sulfate	10 mg/m3 TWA (particulate matter containing no asbestos and < 1% crystalline silica)	-	-	15 mg/m3 TWA; 5 mg/m3 TWA (respirable fraction)	-		-
Cellulose.		-	-		-		-
Polystyrene	-	-	-	-	-		-
Quartz	0.025 mg/m3 TWA (respirable fraction)	-	-	((250)/(%SiO ₂ + 5) mppcf TWA (respirable)); ((10)/(%SiO ₂ + 2) mg/m3 TWA (respirable)); ((30)/(%SiO ₂ + 2) mg/m3 TWA (total dust))	-	-	

In addition to the exposure limits referenced above, the following non-specific limits for dust apply to this product; OSHA, 15 mg/m3-TWA or Total Dust and 5 mg/m3-TWA as Respirable Dust, ACGIH, 10 mg/m3-TWA as Total Dust and 3 mg/m3-TWA as Respirable Dust.

EXPOSURE GUIDELINES (CANADA)

Employers should consult local Provincial regulatory limits for exposure guidelines which may vary locally.

Engineering Controls: Exhaust fans may be necessary when mixing in enclosed areas.

Personal Protective Equipment:

Respiratory Protection: Wear approved respiratory protection (generally a N-95 dust mask is appropriate) to prevent employee exposure from exceeding the limits specified.

Skin Protection: Work gloves or hand creams are recommended to prevent drying of skin.

Eye Protection: At minimum, safety glasses with side shields should be worn where exposure to excessive dust or spray is likely.

Work/Hygienic Practices: Use good personal hygiene practices.

Use bag opening and disposal procedures which minimize dust release. Equip mixers with dust covers to minimize dust released during mixing cycle. After each work shift, workers should shower with soap and water. Work clothing should be changed daily.

Prior to welding or cutting, product must be removed from steel surfaces in those immediate areas where exposure to excessive heat, applied either directly or through conduction, from cutting or welding operations is possible.

All trades should minimize the release of dust during removal of materials by:

- Wetting using water, prior to its removal.
- Removing small areas of fireproofing at one time.
- Maintaining a clean worksite.

Quartz (Crystalline silica) is a naturally-occurring mineral that is commonly contained in materials that are mined from the earth's surface such as sand, limestone, clay and gypsum (Calcium sulfate). Total quartz is a value usually representing the combined fractions of large, non-respirable sized particles and of respirable sized particles (less than ten microns in aerodynamic diameter). It is only the respirable fraction of total quartz that is recognized as hazardous by professionals in the field of Occupational Health and by most regulatory agencies.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Solid
Appearance/Odor:	Light gray or grayish brown, Little to no odor.
Odor Threshold: (ppm)	Not Determined
pH:	Not Available
Vapor Pressure: (Mm Hg)	Unknown
Vapor Density: (Air = 1)	Unknown
Solubility In Water:	Unknown
Specific Gravity: (Water = 1)	Not Available
Evaporation Rate: (Butyl Acetate = 1)	Unknown
Boiling Point:	Not Applicable
Viscosity:	Unknown

W. R. GRACE**MATERIAL SAFETY DATA SHEET**

Product Name: MK-6HY EXP0.25, MK-6HY EXP0.50

MSDS ID Number: Z-01787

MSDS Date: 06/17/2010

Bulk Density: (Pounds/Cubic Foot)(Pcf) 12-16 PCF
% Volatiles (gr/L): (70°F) (21°C) Not Available

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Stable
Conditions To Avoid: None known for this product.
Hazardous Polymerization: Will not polymerize.
Hazardous Decomposition Products: Carbon dioxide, Carbon monoxide and Monomers (C8H8) and various polymers (C8H8). Temperatures in excess of 4000°F from cutting or welding operations may generate Sulfur dioxide. Upon complete combustion, Carbon monoxide and Carbon dioxide are released.

SECTION 11 - TOXICOLOGICAL INFORMATION

<u>Ingredient(No data unless listed.)</u>	<u>CAS Number</u>	<u>LD50 and LC50</u>
Calcium Carbonate.	1317-65-3	Oral LD50 Rat: 6450 mg/kg
Cellulose.	65996-61-4	Inhalation LC50 Rat: >5800 mg/m3/4H; Oral LD50 Rat: >5 g/kg; Dermal LD50 Rabbit: >2 g/kg

Carcinogenicity:

Ingredient	IARC Group 1	IARC Group 2A	IARC Group 2B	NTP Known	NTP Suspect	OSHA
Calcium Carbonate.	No	No	No	No	No	No
Calcium sulfate	No	No	No	No	No	No
Cellulose.	No	No	No	No	No	No
Polystyrene	No	No	No	No	No	No
Quartz	Yes	No	No	Yes	No	Yes

Mutagenicity: Not applicable.
Teratogenicity: Not applicable.
Reproductive Toxicity: Not applicable.

SECTION 12 - ECOLOGICAL INFORMATION

Environmental Fate: No data available for product.
Ecotoxicity: No data available for product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Procedures: Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing waste for disposal. According to EPA (40 CFR § 261), waste of this product is not defined as hazardous. Dispose of waste in accordance with all applicable regulations. Wastes of this product such as empty bags and excess material are typically not defined as hazardous.

SECTION 14 - TRANSPORTATION INFORMATION

Proper Shipping Name: Not Applicable
UN/NA Number: Not Applicable
Domestic Hazard Class: Nonhazardous
Surface Freight Classification: Wall Plaster
Label/Placard Required: Not Applicable

SECTION 15 - REGULATORY INFORMATION**REGULATORY CHEMICAL LISTS:**

CERCLA (Comprehensive Response Compensation and Liability Act):
(None present unless listed below)

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>	<u>CERCLA RQ</u>
SARA Title III (Superfund Amendments and Reauthorization Act)			

SARA Section 312/Tier I & II Hazard Categories:
Health Immediate (acute) Yes

