

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: GRACE Labor Saver
MSDS ID Number: MP-90316

MSDS Date: 10/15/04

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: GRACE Labor Saver
MSDS Number: MP-90316
Cancelled MSDS Number: MP-90128
MSDS Date: 10/15/04
Chemical Family Name: Tall Oil, Mineral Oil Mixture.
Product Use:
Chemical Formula: Mixture-NA
CAS # (Chemical Abstracts Service Number): Mixture-NA

Manufactured by:

W.R.Grace & Co.-Conn. 62 Whittemore Avenue Cambridge, MA 02140	Grace Canada, Inc. 294 Clements Road West Ajax, Ontario L1S 3C6
--	---

In Case of Emergency Call:

In USA: (617) 876-1400 In Canada: (905) 683-8561

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS#	Percent (max)
Fatty acids, tall-oil	061790-12-3	1-10
White mineral oil, petroleum	008042-47-5	50-100

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview:

Warning!

Causes eye burns.
Causes skin irritation.
Causes digestive tract burns if ingested.

HMIS Rating:

Health:	2
Flammability:	0
Reactivity:	0
Personal Protective Equipment:	B (See Section 8)

Potential Health Effects:

Inhalation:

Causes respiratory tract irritation. If prolonged exposure to vapor or mist occurs, effects may be more severe resulting in coughing and breathing difficulties.
Effects include: No other effects expected unless listed below.

Eye Contact:

Eye contact causes burns.

Skin Contact:

Skin contact causes irritation.
Prolonged skin contact can result in burns.

Skin Absorption:

Not expected to be harmful if absorbed through the skin.

Ingestion:

Harmful if ingested.
If ingested, causes burns to the linings of the mouth, esophagus and stomach.
Effects include: Nausea, pulmonary edema (from aspiration into the lungs from vomiting), diarrhea and digestive tract irritation.

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: GRACE Labor Saver
MSDS ID Number: MP-90316

MSDS Date: 10/15/04

SECTION 4 - FIRST AID MEASURES:

Skin Contact:

Wash with soap and water.
If discomfort or irritation persists, consult a physician.
Remove contaminated clothing and wash before reuse.

Eye Contact:

Flush eyes with water for at least 15 minutes while holding eyelids open.
Get immediate medical attention.

Ingestion:

Do not induce vomiting.
Never give anything by mouth to an unconscious person.
If discomfort or irritation persists, consult a physician.

Inhalation:

If symptoms develop, get fresh air. If symptoms persist, consult a physician.
If breathing has stopped, give artificial respiration then oxygen if needed.

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

Flash Point:	250°F
Flash Point Method:	Not Applicable
Lower Explosion Limit:	Not Available
Upper Explosion Limit:	Not Available
Auto-Ignition Temperature:	Not Available

NFPA Rating:

Health:	0
Flammability:	1
Reactivity:	0

Extinguishing Media: In case of fire, use water spray, dry chemical, Carbon dioxide or foam.

Special Fire Fighting Procedures:

Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to vapors or products of combustion exist. Water may be used to cool containers to prevent pressure build-up and possible auto-ignition or explosion. Avoid breathing hazardous vapors or products of combustion, keep upwind. Isolate area and keep unnecessary people away. Prevent run-off from fire control or dilution from entering streams or drinking water supplies.

No special procedures specific to this product.

Unusual Fire and Explosion Hazards:

None unless noted below.

SECTION 6 - ACCIDENTAL RELEASE MEASURES:

Spills/Leaks:

Use proper personal protective equipment. Do not flush to sewer or allow to enter waterways. Keep unnecessary people away.
Contain and/or absorb spill with inert material (i.e. sand, vermiculite) then place in a suitable container.
For large spills, dike area and pump waste material into closed containers for disposal or reclamation.

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: GRACE Labor Saver
MSDS ID Number: MP-90316

MSDS Date: 10/15/04

SECTION 7 - HANDLING AND STORAGE

Precautionary Measures:

Do not cut, drill or weld on or near containers whether full or empty.
Avoid contact with eyes, skin and clothing.
Practice good personal hygiene to avoid ingestion.
Use only with adequate ventilation.
Wash clothing before reuse.
FOR PROFESSIONAL USE ONLY. KEEP OUT OF CHILDREN'S REACH.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT

EXPOSURE GUIDELINES (US)

Ingredient	ACGIH TLV			OSHA PEL			Other
	TWA	STEL	Ceiling	TWA	STEL	Ceiling	
Fatty acids, tall-oil	-	-	-	-	-	-	-
White mineral oil, petroleum	-	-	-	-	-	-	-

EXPOSURE GUIDELINES (CANADA)

Employers should consult local Provincial regulatory limits for exposure guidelines which may vary locally.

Engineering Controls: Not generally required.

Personal Protective Equipment:

Respiratory Protection: Respiratory protection is not normally required. However, a chemical cartridge respirator with organic vapor cartridge and a prefilter for dusts/mits is required at or above the applicable exposure limits (Consult above Exposure Guidelines). If no limits exist, use an approved respirator whenever a vapor or mist is generated or if respiratory irritation occurs. Supplied air respirator (SCBA) is required at exposure levels above the capabilities of a chemical cartridge respirator.

Skin Protection: Rubber or other impervious gloves should be worn to prevent skin contact.

Eye Protection: At minimum, safety glasses with side shields should be worn where exposure to excessive dust or spray is likely.

Work/Hygienic Practices: Use good personal hygiene practices.
None beyond those noted above.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Appearance/Odor:	Clear to amber liquid with virtually no odor.
Odor Threshold: (ppm)	Not Determined
pH:	Not Available
Vapor Pressure: (Mm Hg)	<.5mm
Vapor Density: (Air = 1)	Not Applicable
Solubility In Water:	Negligible
Specific Gravity: (Water = 1)	0.84
Evaporation Rate: (Butyl Acetate = 1)	NIL @ 25°C
Boiling Point:	>450°F
Viscosity:	Unknown
Bulk Density: (Pounds/Cubic Foot)(Pcf)	Not Applicable
% Volatiles (gr/L): (70°F) (21°C)	NIL @ 25°C

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: GRACE Labor Saver
MSDS ID Number: MP-90316

MSDS Date: 10/15/04

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Stable
Conditions To Avoid: None known for this product.
Hazardous Polymerization: Will not polymerize.
Hazardous Decomposition Products: None known for this product.

SECTION 11 - TOXICOLOGICAL INFORMATION

Ingredient(No data unless listed.) **CAS Number** **LD50 and LC50**

Carcinogenicity:

Ingredient	IARC Group 1	IARC Group 2A	IARC Group 2B	NTP Known	NTP Suspect	OSHA
Fatty acids, tall-oil	No	No	No	No	No	No
White mineral oil, petroleum	No	No	No	No	No	No

Mutagenicity: Not applicable.
Teratogenicity: Not applicable.
Reproductive Toxicity: Not applicable.

SECTION 12 - ECOLOGICAL INFORMATION

Environmental Fate: No data available for product.
Ecotoxicity: No data available for product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Procedures:

Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing waste for disposal. According to EPA (40 CFR § 261), waste of this product is not defined as hazardous. Dispose of waste in accordance with all applicable regulations. Oil spills released directly to waterways may be subject to National Response Center (1-800-424-8802) reporting. Immediately contact your company's environmental coordinator or Grace Environmental Health and Safety Department.

SECTION 14 - TRANSPORTATION INFORMATION

Proper Shipping Name: Not Applicable
UN/NA Number: Not Applicable
Domestic Hazard Class: Nonhazardous
Surface Freight Classification: Concrete Surface Curing Compound.
Label/Placard Required: Not Applicable

SECTION 15 - REGULATORY INFORMATION

REGULATORY CHEMICAL LISTS:

CERCLA (Comprehensive Response Compensation and Liability Act):
(None present unless listed below)

Chemical Name **CAS #** **Wt %** **CERCLA RQ**

SARA Title III (Superfund Amendments and Reauthorization Act)

SARA Section 312/Tier I & II Hazard Categories:

Health Immediate (acute) Yes
Health Delayed (chronic) No
Flammable No
Reactive No
Pressure No

