

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Mortar Kick
MSDS ID Number: MP-90172

MSDS Date: 10/21/2002

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Mortar Kick
MSDS Number: MP-90172
Cancelled MSDS Number: MP-90135
MSDS Date: 10/21/2002
Chemical Family Name: Aqueous Solution of Calcium Nitrate
Product Use: Masonry, Concrete Additive
Chemical Formula: Mixture-NA
CAS # (Chemical Abstracts Service Number): Mixture-NA

Manufactured by:

W.R.Grace & Co.-Conn.
62 Whittemore Avenue
Cambridge, MA 02140

Grace Canada, Inc.
294 Clements Road West
Ajax, Ontario L1S 3C6

In Case of Emergency Call:

In USA: (617) 876-1400 In Canada: (905) 683-8561

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS#	Percent (max)
Calcium nitrate	010124-37-5	25-50

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview:

Caution!

Causes severe eye irritation.
Causes skin irritation.
May be fatal if ingested.

HMIS Rating:

Health: 2
Flammability: 1
Reactivity: 0
Personal Protective Equipment: B (See Section 8)

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Mortar Kick
MSDS ID Number: MP-90172

MSDS Date: 10/21/2002

Potential Health Effects:

Inhalation:

Acute inhalation not expected to result in adverse effects.

If inhaled as a vapor or mist, causes irritation, sore throat, coughing and breathing difficulty.

Effects include: Coughing and shortness of breath.

Eye Contact:

Eye contact can cause severe irritation.

Prolonged eye contact can result in tissue damage.

Skin Contact:

Skin contact causes irritation.

Prolonged skin contact can result in irritation causing redness and itching.

Skin Absorption:

Not expected to be harmful if absorbed through the skin.

Ingestion:

Harmful or fatal if ingested.

Effects include: No other effects expected unless listed below.

Large amounts of nitrates/nitrites may cause nausea, vomiting, cyanosis (due to methemoglobin formation), abnormally slow respiration, collapse and coma. Repeated small doses may cause a fall in blood pressure, rapid pulse, headache and visual disturbances. .

SECTION 4 - FIRST AID MEASURES:

Skin Contact:

Wash with soap and water.

If discomfort or irritation persists, consult a physician.

Remove contaminated clothing and wash before reuse.

Eye Contact:

Flush eyes with water for at least 15 minutes while holding eyelids open.

Get immediate medical attention.

Ingestion:

Do not induce vomiting.

Never give anything by mouth to an unconscious person.

Call a physician or poison control center immediately.

Inhalation:

If symptoms develop, get fresh air. If symptoms persist, consult a physician.

If breathing has stopped, give artificial respiration then oxygen if needed.

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Mortar Kick
MSDS ID Number: MP-90172

MSDS Date: 10/21/2002

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

Flash Point:	Not Flammable
Flash Point Method:	Not Applicable
Lower Explosion Limit:	Not Available
Upper Explosion Limit:	Not Available
Auto-Ignition Temperature:	Not Available

NFPA Rating:

Health:	1
Flammability:	0
Reactivity:	0

Extinguishing Media: In case of fire, use water spray, dry chemical, Carbon dioxide or foam.

Special Fire Fighting Procedures:

Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to vapors or products of combustion exist. Water may be used to cool containers to prevent pressure build-up and possible auto-ignition or explosion. Avoid breathing hazardous vapors or products of combustion, keep upwind. Isolate area and keep unnecessary people away. Prevent run-off from fire control or dilution from entering streams or drinking water supplies.

No special procedures specific to this product.

Unusual Fire and Explosion Hazards:

This material, if dried, will become an oxidizer which may provide oxygen to combustible materials.

SECTION 6 - ACCIDENTAL RELEASE MEASURES:

Spills/Leaks:

Use proper personal protective equipment. Do not flush to sewer or allow to enter waterways. Keep unnecessary people away.

Do not dry this material. If dried, this product would be an oxidizer and classified as a reactive waste according to the EPA (40 CFR § 261.3) Liquid waste is not classified as hazardous by the EPA.

Contain and/or absorb spill with inert material (i.e. sand, vermiculite) then place in a suitable container. For large spills, dike area and pump waste material into closed containers for disposal or reclamation.

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Mortar Kick
MSDS ID Number: MP-90172

MSDS Date: 10/21/2002

SECTION 7 - HANDLING AND STORAGE

Precautionary Measures:

Avoid contact with eyes, skin and clothing.

Do not take internally.

Practice good personal hygiene to avoid ingestion.

Use only with adequate ventilation.

Wash clothing before reuse.

FOR PROFESSIONAL USE ONLY. KEEP OUT OF CHILDREN'S REACH.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT

EXPOSURE GUIDELINES (US)

Ingredient	ACGIH TLV			OSHA PEL			Other
	TWA	STEL	Ceiling	TWA	STEL	Ceiling	
Calcium nitrate	-	-	-	-	-	-	-

EXPOSURE GUIDELINES (CANADA)

Employers should consult local Provincial regulatory limits for exposure guidelines which may vary locally.

Engineering Controls: Not generally required.

Personal Protective Equipment:

Respiratory Protection: Respiratory protection is not normally required. However, a chemical cartridge respirator with organic vapor cartridge and a prefilter for dusts/mists is required at or above the applicable exposure limits (Consult above Exposure Guidelines). If no limits exist, use an approved respirator whenever a vapor or mist is generated or if respiratory irritation occurs. Supplied air respirator (SCBA) is required at exposure levels above the capabilities of a chemical cartridge respirator.

Skin Protection: Rubber or other impervious gloves should be worn to prevent skin contact.

Eye Protection: At minimum, safety glasses with side shields should be worn where exposure to excessive dust or spray is likely.

Work/Hygiene Practices: Use good personal hygiene practices. None beyond those noted above.

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Mortar Kick
MSDS ID Number: MP-90172

MSDS Date: 10/21/2002

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Appearance/Odor:	Dark green color, no odor
Odor Threshold: (ppm)	Not Determined
pH:	3.0-8.0
Vapor Pressure: (Mm Hg)	Not Applicable
Vapor Density: (Air = 1)	Not Applicable
Solubility In Water:	Dilutable in all proportions
Specific Gravity: (Water = 1)	1.4
Evaporation Rate: (Butyl Acetate = 1)	Not Applicable
Boiling Point:	>100°C/212°F
Viscosity:	Unknown
Bulk Density: (Pounds/Cubic Foot)(Pcf)	Not Applicable
% Volatiles (gr/L): (70°F) (21°C)	60% (as Water)

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability:	Stable
Conditions To Avoid:	Organic materials, Reducing agents, Most metals, ammonia and hydrazine.
Hazardous Polymerization:	Will not polymerize.
Hazardous Decomposition Products:	Oxides of nitrogen.

SECTION 11 - TOXICOLOGICAL INFORMATION

<u>Ingredient(No data unless listed.)</u>	<u>CAS Number</u>	<u>LD50 and LC50</u>
Calcium nitrate	010124-37-5	Oral LD50 Rat : 302 mg/kg

Carcinogenicity:

Ingredient	IARC Group 1	IARC Group 2A	IARC Group 2B	NTP Known	NTP Suspect	OSHA
Calcium nitrate	No	No	No	No	No	No

Mutagenicity:	Not applicable.
Teratogenicity:	Not applicable.
Reproductive Toxicity:	Not applicable.

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Mortar Kick
MSDS ID Number: MP-90172

MSDS Date: 10/21/2002

SECTION 12 - ECOLOGICAL INFORMATION

Environmental Fate: No data available for product.
Ecotoxicity: No data available for product.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Procedures:

Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing waste for disposal. According to EPA (40 CFR § 261), waste of this product is not defined as hazardous. Dispose of waste in accordance with all applicable regulations.

Do not dry this material. If dried, this material would be an oxidizer and classified as a reactive waste #D001 according to the EPA (40 CFR § 261). Liquid waste is not defined as hazardous by EPA.

SECTION 14 - TRANSPORTATION INFORMATION

Proper Shipping Name: Not Applicable
UN/NA Number: Not Applicable
Domestic Hazard Class: Nonhazardous
Surface Freight Classification: Cement or Masonry Plasticizer and Water Reducing Compound
Label/Placard Required: Not Applicable

SECTION 15 - REGULATORY INFORMATION

REGULATORY CHEMICAL LISTS:

CERCLA (Comprehensive Response Compensation and Liability Act):
(None present unless listed below)

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>	<u>CERCLA RQ</u>
----------------------	--------------	-------------	------------------

SARA Title III (Superfund Amendments and Reauthorization Act)

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Mortar Kick
MSDS ID Number: MP-90172

MSDS Date: 10/21/2002

SARA Section 312/Tier I & II Hazard Categories:

Health Immediate (acute)	Yes
Health Delayed (chronic)	No
Flammable	No
Reactive	No
Pressure	No

302 Reportable Ingredients (Identification Threshold 1%.):

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>	<u>SARA 302 TPQ</u>
----------------------	--------------	-------------	-------------------------

313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
Nitrate compounds	RR-01770-9	40

National Volatile Organic Compound Emission Standards For Architectural Coatings:

Volatile Organic Content: (gr/L) Not Applicable

WHMIS Classification(s): D2 B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR). This MSDS contains all the information required by the CPR.

State Regulatory Information:

<u>California Proposition 65:</u>	This product does not contain substances known to the state of California to cause cancer, birth defects or other reproductive harm.
--	--

Massachusetts Hazardous Substance List(Identification threshold 0.001%(1ppm)):

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
----------------------	--------------	-------------

New Jersey Hazardous Substance List(Identification threshold (0.1%)):

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
Nitrate compounds	RR-01770-9	40

