

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Procor 10 Part A
MSDS ID Number: M-85744

MSDS Date: 12/30/04

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Procor 10 Part A
MSDS Number: M-85744
Cancelled MSDS Number: M-85721
MSDS Date: 12/30/04
Chemical Description: Naphthenic Oils and Inorganic Fill
Product Use: Waterproofing Products
CAS # (Chemical Abstracts Service Number): Mixture-NA

Manufactured by:

W.R.Grace & Co.-Conn. 62 Whittemore Avenue Cambridge, MA 02140	Grace Canada, Inc. 294 Clements Road West Ajax, Ontario L1S 3C6
--	---

In Case of Emergency Call: (617) 876-1400

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS#	Percent (max)
Calcium oxide	001305-78-8	25-50
Castor oil based ester	NJ801415063P	1-10
Distillates, petroleum, hydrotreated heavy naphthenic	064742-52-5	50-100
Quartz	014808-60-7	1-10
Zinc oxide	001314-13-2	1-10

SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview:

Warning!

Causes eye irritation.
Causes skin irritation.
Causes digestive tract irritation if ingested.
Product supplied as two component package and part A reacts with Part B and with water.
A&B (and A with water) Reaction is exothermic, releasing heat. Fumes may also be released if unused mixed product is allowed to sit in containers or if thicknesses exceed 120 mils.
Mixed A&B product may reach temperatures of 300°F.
Reacting material is sticky and will adhere to skin.
Contact with hot materials will result in burns.
Do not seal containers once mixed with component B or contaminated with water. Sealed containers may explode due to pressure from the reaction.

HMIS Rating:

Health:	1
Flammability:	1
Reactivity:	1
Personal Protective Equipment:	B,G (See Section 8)

Potential Health Effects:

Inhalation: When mixed material is allowed to react in a container, temperatures up to 300°F can be reached, liberating water vapor, carbon disulfide and other hydrocarbons. Inhalation of these materials can cause irritation.

Prolonged inhalation can cause lung damage.
Effects include: Flu-like symptoms (metal fume fever).

Eye Contact: Eye contact causes irritation.

Skin Contact: Skin contact causes irritation. Product reacts with other component (component B) and also with water. Contact with hot material will result in burns. Reacting material is sticky and hot and will adhere to skin if touched before fully cured.

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Procor 10 Part A

MSDS ID Number: M-85744

MSDS Date: 12/30/04

Skin Absorption: Not expected to be harmful if absorbed through the skin.

Ingestion: Due to the physical nature of this product, ingestion of this product is not likely. If ingested, causes irritation to the linings of the mouth, esophagus and stomach.

Effects include the following: Nausea, vomiting, sneezing, coughing, labored breathing and burns.

SECTION 4 - FIRST AID MEASURES:

Skin Contact: In case of skin contact, clean fingernails and wash skin with soap and water. If residue remains, clean with waterless hand-cleaners or abrasive soap. Never use solvents.

If discomfort or irritation persists, consult a physician.

Remove contaminated clothing and wash before reuse.

Eye Contact: If discomfort or irritation persists, consult a physician.

Flush eyes with water for at least 15 minutes while holding eyelids open.

Ingestion: If ingested, consult a physician.

Never give anything by mouth to an unconscious person.

Do not induce vomiting.

Inhalation: If symptoms develop, get fresh air.

If symptoms persists, consult a physician.

If breathing has stopped, give artificial respiration then oxygen if needed.

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

Flash Point: Not Determined

Flash Point Method: Not Applicable

Lower Explosion Limit: Not Available

Upper Explosion Limit: Not Available

Auto-Ignition Temperature: Not Available

NFPA Rating:

Health: 1

Flammability: 1

Reactivity: 1

Extinguishing Media: In case of fire, use dry chemical, Carbon dioxide or foam.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to vapors or products of combustion exist. Water may be used to cool containers to prevent pressure build-up and possible auto-ignition or explosion. Avoid breathing hazardous vapors or products of combustion. Keep upwind. Isolate area and keep unnecessary people away. Prevent run-off from fire control or dilution from entering streams or drinking water supplies.

Unusual Fire and Explosion Hazards: None unless noted below.

SECTION 6 - ACCIDENTAL RELEASE MEASURES:

Spills/Leaks: Use proper personal protective equipment. According to EPA (40 CFR § 261.3) waste of this product is not defined as hazardous. Do not flush to sewer or allow to enter waterways. Keep unnecessary people away. Oil spills released directly to waterways may be subject to reporting requirements. Immediately contact your company's environmental coordinator or the Grace Environmental Health and Safety Department.

SECTION 7 - HANDLING AND STORAGE

Precautionary Measures: Avoid contact with eyes, skin and clothing.

Do not take internally.

Practice good personal hygiene to avoid ingestion.

Use only with adequate ventilation.

Wash clothing before reuse.

Wear respiratory protection indoors or where ventilation is inadequate.

Product supplied as two component package and part A reacts with part B (and with water). A&B (or A & water) Reaction is exothermic, releasing heat. Fumes may also be released if unused

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Procor 10 Part A
 MSDS ID Number: M-85744

MSDS Date: 12/30/04

mixed product is allowed to sit in containers or if thicknesses exceeds 120 mils.
 Reaction product is sticky and will adhere to skin.
 Contact with hot material will result in burns.
 Do not touch material once thickening (reaction) begins, and until cured and cool.
 Procor 10, parts A and B are supplied in mixing pails. Once component A&B are mixed, use all product within 30-60 minutes of mixing to avoid heat build up due to exothermic reaction (release of heat and fumes).
 Reaction times may vary depending upon temperature and mixing conditions.
 Promptly cleanse hands after handling.
FOR PROFESSIONAL USE ONLY. KEEP OUT OF CHILDREN'S REACH.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTIVE EQUIPMENT

EXPOSURE GUIDELINES (US)

Ingredient	ACGIH TLV			OSHA PEL			Other
	TWA	STEL	Ceiling	TWA	STEL	Ceiling	
Calcium oxide	2 mg/m3 TWA	-	-	5 mg/m3 TWA (not in effect as a result of reconsideration)	-		
Castor oil based ester	-	-	-	-	-		
Distillates, petroleum, hydrotreated heavy naphthenic	-	-	-	-	-		
Quartz	0.05 mg/m3 TWA (respirable fraction)	-	-	0.1 mg/m3 TWA (respirable dust)	-		
Zinc oxide	2 mg/m3 TWA (respirable fraction)	10 mg/m3 STEL (respirable fraction)	-	5 mg/m3 TWA (fume); 10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	10 mg/m3 STEL (fume)		

Respirable Quartz (Crystalline silica) can result in lung disease (i.e. silicosis and or lung cancer). However, due to the physical nature of this product (liquid) exposures are not expected unless after product dries it is abraded and airborne dust is created.

EXPOSURE GUIDELINES (CANADA)

Employers should consult local Provincial regulatory limits for exposure guidelines which may vary locally.

Engineering Controls: Provide forced ventilation and/or local exhaust ventilation to prevent vapor build-up during application. This is particularly important in enclosed or confined areas where natural ventilation may not be adequate. Provide enough ventilation to maintain exposure levels below regulatory limits.

Personal Protective Equipment:

Respiratory Protection: Respiratory protection is not normally required in well ventilated areas. However, indoors or where ventilation is inadequate, the use of respirators equipped with organic vapor cartridges is required. The specified respirator may not adequately protect against exposure during actual working conditions which must be assessed before and throughout product application as work progresses. (See Work/Hygienic Practices.)

Skin Protection: Impervious (PVC, or nitrile) gloves should be worn anytime direct contact is possible.

Eye Protection: Safety glasses or goggles should be worn.

Work/Hygienic Practices: Use good personal hygiene practices.

Carbon disulfide and other potentially harmful gases, vapors and fumes may evolve as a result of exothermic reactions ("hot product") when components are mixed. Carbon disulfide may be detected by odor at about 1 ppm, but the ability to smell fatigues (diminishes) rapidly, therefore, odor does not serve as a good warning property. If eye or respiratory irritation is present, or if a

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Procor 10 Part A

MSDS ID Number: M-85744

MSDS Date: 12/30/04

foul odor is detected, you may be experiencing exposure to Carbon disulfide and other organics. Leave the area immediately and seek fresh air.

Quartz (Crystalline silica) is a naturally-occurring mineral that is commonly contained in materials that are mined from the earth's surface such as sand, limestone, clay and gypsum (Calcium sulfate). Total quartz is a value usually representing the combined fractions of large, nonrespirable sized particles and of respirable sized particles (less than ten microns in aerodynamic diameter). It is only the respirable fraction of total quartz that is recognized as hazardous by professionals in the field of Occupational Health and by most regulatory agencies. This product contains compounds subject to exposure guidelines and/or identified as carcinogens (See section 8 and 11).

Due to the physical nature of this product, (liquid) these compounds are not likely to reach exposure limits unless after product dries, it is abraded and airborne dust is created.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Appearance/Odor:	A brownish semi-viscous liquid with an aromatic odor.
Odor Threshold: (ppm)	Not Determined
pH:	Not Applicable
Vapor Pressure: (Mm Hg)	Not Determined
Vapor Density: (Air = 1)	Not Determined
Solubility In Water:	Insoluble
Specific Gravity: (Water = 1)	~1.28
Evaporation Rate: (Butyl Acetate = 1)	Not Determined
Boiling Point:	Not Determined
Bulk Density: (Pounds/Cubic Foot)	~83
% Volatiles (70°F) (21°C)	Not Determined

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability:	Stable
Conditions To Avoid:	Heat, Strong oxidizers, Strong acids, Organic materials, Water, phosphorous pentoxide, magnesium, rubber, linseed oil, hydrogen flouride and boric acid.
Hazardous Polymerization:	Will not polymerize.
Hazardous Decomposition Products:	Carbon dioxide and toxic fumes of zinc oxide.

SECTION 11 - TOXICOLOGICAL INFORMATION

<u>Ingredient(No data unless listed.)</u>	<u>CAS Number</u>	<u>LD50 and LC50</u>
Zinc oxide	001314-13-2	Oral LD50 Mouse: 7950 mg/kg

Carcinogenicity:

Ingredient	IARC Group 1	IARC Group 2A	IARC Group 2B	NTP Known	NTP Suspect	OSHA
Calcium oxide	No	No	No	No	No	No
Castor oil based ester	No	No	No	No	No	No
Distillates, petroleum, hydrotreated heavy naphthenic	No	No	No	No	No	No
Quartz	Yes	No	No	Yes	Yes	Yes
Zinc oxide	No	No	No	No	No	No

Mutagenicity:	Not applicable.
Teratogenicity:	Not applicable.
Reproductive Toxicity:	Not applicable.

SECTION 12 - ECOLOGICAL INFORMATION

Environmental Fate:	No data available for product.
Ecotoxicity:	No data available for product.

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Procor 10 Part A
MSDS ID Number: M-85744

MSDS Date: 12/30/04

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal Procedures: Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing waste for disposal. According to EPA (40 CFR § 261), waste of this product is not defined as hazardous. Dispose of waste in accordance with all applicable regulations.

SECTION 14 - TRANSPORTATION INFORMATION

Proper Shipping Name:	Not Applicable
UN/NA Number:	Not Applicable
Domestic Hazard Class:	Non Hazardous
Surface Freight Classification:	Adhesive Cement N.O.I.
Label/Placard Required:	Not Applicable

SECTION 15 - REGULATORY INFORMATION

REGULATORY CHEMICAL LISTS:

CERCLA (Comprehensive Response Compensation and Liability Act):
(None present unless listed below)

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>	<u>CERCLA RQ</u>
----------------------	--------------	-------------	------------------

SARA Title III (Superfund Amendments and Reauthorization Act)

SARA Section 312/Tier I & II Hazard Categories:

Health Immediate (acute)	Yes
Health Delayed (chronic)	No
Flammable	No
Reactive	No
Pressure	No

302 Reportable Ingredients (Identification Threshold 1%):

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>	<u>SARA 302 TPQ</u>
----------------------	--------------	-------------	---------------------

313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
Zinc compounds	RR-00578-7	3.10831

National VOC Emissions Standard for Architectural Coatings:

Volatile Organic Content gr/l 75 g/l (as applied)

WHMIS Classification(s): D2 B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR). This MSDS contains all the information required by the CPR.

State Regulatory Information:

California Proposition 65: This product may, upon mixing, release small amounts of Carbon disulfide, a substance found on California's Proposition 65 list.

Massachusetts Hazardous Substance List(Identification threshold 0.001%(1ppm)):

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
Quartz	014808-60-7	6.72

New Jersey Hazardous Substance List(Identification threshold (0.1%)):

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
Zinc compounds	RR-00578-7	3.10831

Pennsylvania Hazardous Substance List(Identification threshold 0.01%):

<u>Chemical Name</u>	<u>CAS #</u>	<u>Wt %</u>
----------------------	--------------	-------------

CHEMICAL INVENTORY STATUS:

All chemicals in this product are listed or exempt from listing in the following countries:

W. R. GRACE
MATERIAL SAFETY DATA SHEET

Product Name: Procor 10 Part A

MSDS ID Number: M-85744

MSDS Date: 12/30/04

US	CANADA		EUROPE	AUSTRALIA	JAPAN	KOREA	PHILIPPINES
TSCA	DSL	NDSL	EINECS/ELINCS	AICS	ENCS	ECL	PICCS
Yes	No	Yes	Yes	Yes	Yes	Not Determined	Not Determined

SECTION 16 - OTHER INFORMATION

Non-Hazardous Ingredient Disclosure:

Chemical Name

CAS Number

Prepared by:

EH&S Department

Approved by:

EH&S Department

Approved Date:

12/30/04

Disclaimer:

"The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection."